

PHOTO	DESCRIPTION	Specification Size	Certification
 <p>model: BY300U</p>	<p>Continuous Power: 300W Peak Power: 600W Input Voltage: VDC 12V or 24V Output Voltage: 220-240 VCA / 100-120 VCA USB: DC 5V (MAX. 500 mA) Wave Form: Pure sine wave form Frequency: 50-60 +/- 3Hz Total Harmonic Distortion: <3% Protections: Overload, Overheat, Short- circuit, Low voltage, Overvoltage</p>	<p>205*105*60mm (Size) 515*305*355mm (Carton) color box packing</p>	CE, ROHS
 <p>model: BY500U</p>	<p>Continuous Power: 500W Peak Power: 1000W Input Voltage: VDC 12V or 24V Output Voltage: 220-240 VCA / 100-120 VCA USB: DC 5V (MAX. 500 mA) Wave Form: Pure sine wave form Frequency: 50-60 +/- 3Hz Total Harmonic Distortion: <3% Protections: Overload, Overheat, Short- circuit, Low voltage, Overvoltage</p>	<p>260*105*60mm (Size) 515*305*355mm (Carton) color box packing</p>	CE, ROHS
 <p>model: BY1000U</p>	<p>Continuous Power: 1000W Peak Power: 2000W Input Voltage: VDC 12V or 24V Output Voltage: 220-240 VCA / 100-120 VCA USB: DC 5V (MAX. 500 mA) Wave Form: Pure sine wave form Frequency: 50-60 +/- 3Hz Total Harmonic Distortion: <3% Protections: Overload, Overheat, Short- circuit, Low voltage, Overvoltage</p>	<p>260*150*75mm (Size) 625*305*375mm (Carton) color box packing</p>	CE, ROHS
 <p>model: BY1500U</p>	<p>Continuous Power: 1500W Peak Power: 3000W Input Voltage: VDC 12V or 24V Output Voltage: 220-240 VCA / 100-120 VCA USB: DC 5V (MAX. 500 mA) Wave Form: Pure sine wave form Frequency: 50-60 +/- 3Hz Total Harmonic Distortion: <3% Protections: Overload, Overheat, Short- circuit, Low voltage, Overvoltage</p>	<p>350*150*75mm (Size) 405*370*252mm (Carton) color box packing</p>	CE, ROHS
 <p>model: BY2000U</p>	<p>Continuous Power: 2000W Peak Power: 4000W Input Voltage: VDC 12V or 24V Output Voltage: 220-240 VCA / 100-120 VCA USB: DC 5V (MAX. 500 mA) Wave Form: Pure sine wave form Frequency: 50-60 +/- 3Hz Total Harmonic Distortion: <3% Protections: Overload, Overheat, Short- circuit, Low voltage, Overvoltage</p>	<p>350*150*75mm (Size) 405*370*252mm (Carton) color box packing</p>	CE, ROHS
 <p>model: BY3000U</p>	<p>Continuous Power: 3000W Peak Power: 6000W Input Voltage: VDC 12V or 24V Output Voltage: 220-240 VCA / 100-120 VCA USB: DC 5V (MAX. 500 mA) Wave Form: Pure sine wave form Frequency: 50-60 +/- 3Hz Total Harmonic Distortion: <3% Protections: Overload, Overheat, Short- circuit, Low voltage, Overvoltage</p>	<p>435*195*87mm (Size) 505*248*295mm (Carton) color box packing</p>	CE, ROHS